

Model No.	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Static Pressure	Noise
	○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	mm H ₂ O	dB(A)

Aluminium Housing with Plastic Impeller



4"

120 x 120 x 38 mm 4-11/16 x 4-11/16 x 1-1/2 in

REC - 22038 A2 T	○	230	50	0.10	18	2650	85	6	43
REC - 22038 B2 T	●	230	50	0.10	18	2750	90	7	43
REC - 22038 A2 W	○	230	50	0.10	18	2650	85	6	43
REC - 22038 B2 W	●	230	50	0.10	18	2750	90	7	43



6"

Ø172 x 150 x 51 mm 6-3/4 x 5-7/8 x 2 in

REC - 21725 A2 W	○	230	50	0.19	27	2600	180	14	52
REC - 21725 B2 W	●	230	50	0.19	27	2650	190	16	52



8"

Ø220 x 60 mm Ø 8-21/32 x 2-3/8 in

REC - 22060 R B2 W	●	230	50	0.40	62	2450	360	22	56
--------------------	---	-----	----	------	----	------	-----	----	----

AC Frame Type



6"

172 x 172 x 55 mm

REC - 27255 A2 W	○	230	50	0.19	27	2600	180	14	52
REC - 27255 B2 W	●	230	50	0.19	27	2650	190	16	52



8"

220 x 220 x 60 mm

REC - 22060 S A2 W	○	230	50	0.40	62	2400	360	22	56
REC - 22060 S B2 W	●	230	50	0.40	62	2450	360	22	56